

Tremco AVC Membrane Primers

Quick Drying Primers for Use with Tremco AVC Membranes

PRODUCT DESCRIPTION:

Tremco AVC Membrane Primer is an SIS rapid-curing adhesive primer formulated to prepare and promote adhesion to sound, clean and dry structural decks and subdecks of concrete, metal, wood and exterior grade sheathing panels. Tremco AVC Primer should be applied with a roller or brush prior to application of Tremco AVC Membrane. Apply Tremco AVC Membrane after Tremco AVC Primer dries to a non-transferable tacky film. (approximately 15 minutes at 23°C at 50% relative humidity)

Tremco AVC Membrane Primer (WB) is a water-based (WB), quick drying modified bitumen primer to be applied prior to the application of Tremco AVC Membrane. WB promotes adhesion to sound, clean and dry structural decks and subdecks of concrete, metal, wood and exterior grade sheathing panels. Apply Tremco AVC Membrane Primer (WB) with a brush or roller. Tremco AVC Membrane should not be applied to Tremco AVC Membrane Primer (WB) until it is completely dry (approximately 45 minutes at 23°C at 50% relative humidity). Stir primer before use. Do not apply Tremco AVC Membrane Primer (WB) below 7°C. (45°F).

Coverage Rate:

Approximately 6m²/Lm (250 ft²/gal) depending on porosity and texture of surface.

Packaging:

18.9L (5 gal) pails

Physical Performance Characteristics		
Tremco AVC Membrane Primer		
Property	Typical Value	Test Method
% Total solids	44.5-46.5	
Viscosity	500-750 cps	
Specific gravity	0.89-0.91	
Appearance	Dark green, light syrupy liquid	
Tremco AVC Membrane Primer (WB)		
Property	Typical Value	Test Method
% Total solids	53.3 (4 lb.)	
Viscosity	2-3600 cps	
Specific gravity	0.89-0.91	
Appearance		

Precautions:

Users must read container labels and Material Safety Data Sheets for health and safety precautions prior to use.

Availability and Cost: Contact your local Tremco Roofing Representative for pricing and availability. For the name and number of your Representative, call the Roofing Division at 416/421-3300 or 800/263-6046.

Maintenance: Your local Tremco Roofing Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

Guarantee/Warranty: Tremco Inc. warrants Tremco AVC Membrane Primers to be free of defects and to meet published physical properties when tested according to ASTM and Tremco standards. Under this warranty, any Tremco AVC Membrane Primers product that is proved to be defective when applied in accordance to our written instructions, and in applications recommended by Tremco as suitable for this product will be replaced with like product at no charge. THIS IS BUYERS SOLE AND EXCLUSIVE REMEDY.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty shall be IN LIEU OF any other warranty, express or implied, including but not limited to, any implied warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

TREMCO

Roofing & Weatherproofing Peace of Mind™

Technical Services: Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the services of the Tremco Technical Service staff.

Statement of Policy and Responsibility: Tremco takes responsibility for furnishing quality materials and for providing specifications and recommendations for their proper installation.

As neither Tremco itself nor its Representatives practice architecture or engineering, Tremco offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure or its ability to support a planned installation properly, the Owner should obtain the opinion of competent structural engineers before proceeding. Tremco accepts no liability for any structural failure or for resultant damages, and no Tremco Representative is authorized to vary this disclaimer.

TREMCO

An **RPM** Company

220 Wicksteed Ave
Toronto, ONT M4H 1G7
416-421-3300

3735 Green Road
Beachwood, OH 44122
216-292-5000